

Carbon Monoxide Alarm (CO)



- High-performance electrochemical CO sensor to deliver accurate detection of carbon monoxide leakage and respond quickly
- · Long standby time, low power consumption, 10-year battery life
- Temperature and humidity measurement: Display current temperature and humidity alternately without the presence of CO
- Screen display: Blue backlight function is user-friendly to read information
- · Support low battery warning, one-click silence, and self-test
- Informative and easy-to-read CO concentration display in screen
- · Three indicator lights for displaying device status clearly



System Overview

The Carbon Monoxide Alarm (hereinafter referred to as the Device) responds quickly with high sensitivity, stable performance and low false alarms when there is too much Carbon Monoxide in the air. This Device is able to measure carbon monoxide levels as low as 30 ppm using the high quality sensor. The multi-functional LCD screen displays the temperature and humidity in standby mode, and the carbon monoxide concentration in alarm mode. Once the ambient carbon monoxide concentration reaches the alarm value, the device sounds a loud 85dB alarm and the LED flashes rapidly, alerting users to take immediate action.

Scene

Application scenarios include homes, restaurants, hotels and other places that require Carbon Monoxide detection.


Technical Specification		
Working Principle		
Collection Type	Carbon Monoxide (CO)	
Sensor Type	Electrochemical	
Alarm		
Alarm Type	CO alarm, fault warning, low battery warning	
Alarm Volume	Over 85dB (A) at 3 m (9.84 ft)	
Alarm Mode	Visual and audible alarm	
Silence Function	Support	
Silence Duration	About 9 minutes	
Alarm Response Threshold	50 ppm: 60 min–90 min 100 ppm: 10 min–40 min 300 ppm: < 3 min	

Technical Specification			
Basic Parameters			
Display	LCD		
Indicator Light	LED (red/yellow/green)		
LED Instruction	Alarm: Red indicator Fault: Yellow indicator Power: Green indicator		
Power Supply			
Battery Life	10 years		
Power Source	3V CR17450A lithium battery (non-replaceable)		
Operating Current	Standby Current: ≤20uA Alarm Current: ≤20mA		
Operating Ambient			
Operating Environment	Indoor use only		
Operating Temperature	-10°C to +40°C (+14°F to +104°F)		
Operating Humidity	≤95% RH (non condensing)		
Environmental Measurement			
Temperature Accuracy	±0.1°C typical		
Humidity Accuracy	±1.5%RH typical		
Appearance			
Color	White		
Material	PC + ABS		
Dimensions	133.5 mm × 63.5 mm × 28.9mm (5.26" × 2.50" × 1.14")		
Weight	123 g (0.28lb)		
Installation	Wall mount/Free standing		




Technical Specification Certification Certifications TUV, CE and UKCA listed Compliance Standard EN 50291-1:2018 and BS EN 50291-1:2018

Dimensions (mm/inch)







4				
	11100888	70000000	990000009990	9 9 8 8 8 9 0 MM
\equiv				
33	1			\
0.0				
~				

Ordering Information			
Туре	Description		
Carbon Monoxide Alarm	Standalone Carbon Monoxide Alarm		